



Length	Mtg. Ctr.	Wattage
18-1/16"	14-1/4"	15T8 (F15T8)
24-1/16"	20-1/4"	14T5, 24T5HO, 17T8
36-1/16"	32-1/4"	21T5, 39T5HO, 25T8
48-1/16"	44-1/4"	28T5, 54T5HO, 32T8

Project Name:	
Type:	Date:
Catalog #:	

Description:

The Nulite 114 series is a solid front task light for limited space areas. Use in work centers, under cabinets, displays and study areas.

Specifications:

Construction: Die formed cold rolled steel housing. All metal parts are finished with a durable baked white enamel paint.

Diffuser: Acrylic clear ribbed diffuser which snaps on and off with ease.

Reflector / Ballast Cover: Reflector pan & ballast cover are finished with high reflectance white. Standard electronic, Class P, ballast.

Lamping: 1 lamp cross-section in nominal 18", 2', 3', or 4' lengths. Luminaire can be ordered with lamp, consult factory.

Mounting: Surface mounting, individually or continuous rows.

Labels: UL / cUL listed. Damp location is optional.

Ordering Information

Sample: 114-132T8-120-ISN-CP3(48")

Series	Lamp	Wattage	Voltage	Ballast	Options
114	1				
		15T8 ¹	UNV	T8 Options	Ballast Factor
		14T5	120	IS (Standard) Instant Start	N Normal (Standard)
		24T5HO	277	PS Program Start	L Low
		17T8		HEIS High Efficiency Instant Start	H High
		21T5		HEPS High Efficiency Program Start	
		39T5HO		T5/T5HO	Ballast Factor
		25T8		PS (Standard) Program Start	N Normal
		28T5		HEPS ² High Efficiency Program Start	
		54T5HO			
		32T8			
					CO Convenience Outlet (120V Only)
					RS Rocker Switch (120V Only)
					TS Turn Switch (120V Only)
					DL Damp Location
					CP3/6 Cord & Plug; 120V, 3-wire (6')

Note:

- 15W T8 not available in universal voltage and only available in ISN ballast.
- Consult factory.