

Project Name:	
Type:	Date:
Catalog #:	

Description:

The Nulite I-06 is an industrial grade luminaire which is ideal for retail, commercial and industrial applications. The I-06 may be surface mounted or suspended, individually or in continuous row.

Specifications:

Construction: Die formed, 22 gauge, cold rolled steel designed for high strength. The housing finish is white baked enamel. End caps snap in for easy installation and can be used for continuous row mounting.

Reflector / Ballast: Reflector is a nominal 4' specular anodized aluminum. Two reflectors for nominal 8' housing. Standard electronic, Class P, ballast. Universal (UNV) voltage ballast is from 120 to 277V.

Lamping: 1 lamp cross-section T5, T5HO or T8. Nominal 8' housing is a tandem lamp configuration. Luminaire can be ordered with lamps, consult factory.

Mounting: Luminaires may be surface mounted or suspended, individually or in continuous row.

Labels: UL / cUL listed. Damp location is optional.

Length	Wattage
46"	28T5, 54T5HO
48"	32T8
92"	28T5-8, 54T5HO-8
96"	32T8-8

Ordering Information


Sample: I-06-154T5HO-UNV-PSN-3C

Series	Lamp	Wattage	Voltage	Ballast	Options	Mounting		
I-06	1	28T5	UNV	T8 Options	Ballast Factor	EM ² Emergency Battery Pack DL Damp Location QW Quick Through Wiring for Continuous Row Applications GLR Fusing		
		54T5HO	120	IS (Standard) Instant Start	N Normal (Standard)		3C 3' Chain Set	
		32T8	277	PS Program Start	L Low		SC Stem & Canopy (specify length)	
		28T5-8	347 ¹	HEIS High Efficiency Instant Start	H High			
		54T5HO-8	480 ¹	HEPS High Efficiency Program Start				
		32T8-8						
					T5/T5HO		Ballast Factor	
					PS (Standard) Program Start		N Normal	
					HEPS ¹ High Efficiency Program Start			
					All Lamp Dimming Options			
			DIM ¹ Dimming					
			SD ¹ Step Dimming					

Notes:


1. Consult factory.
2. Specific voltage must be ordered for this option.

Industrial Options



White threaded stem and matching canopy. Available in lengths from 6" to 10'.

Stem & Canopy Set (SC)





36" lengths of chain, "S" hook, and "Y" hanger. Chain and hook 12 gauge.

Chain Set (3C)



Plan view of KOs on back of channel

All housings have 7/8" KOs on both ends as well as on the back of the channel. In addition, each channel has eyelets and other holes for mounting by various means.

Strip Back Plans T8



Strip Back Plans T5



Specifications and dimensions are subject to change without notification.