



Length	Wattage
22-1/2"	14T5, 24T5HO
34-1/4"	21T5, 39T5HO
46-1/8"	28T5, 54T5HO

Project Name:	
Type:	Date:
Catalog #:	

**Description:**

The Nulite 17N series is a durable petite profile surface mounted lensed luminaire. The opal acrylic lens softens lamp brightness. These luminaires are ideal for corridors, walkways, stairwells, utility rooms and lavatories.

**Specifications:**

**Construction:** Housing is die formed of 20 gauge cold rolled steel with 7/8" end KO. All metal parts are finished with white polyester powder coat paint. Smooth opal acrylic snap-in lens.

**Reflector / Ballast:** Ballast cover/reflector is formed and finished with high reflectance white paint. Standard electronic, Class P, ballast. Universal (UNV) voltage ballast is from 120 to 277V.

**Lamping:** 1 or 2 lamp cross-section T5, 1 lamp cross-section T5HO, in nominal 2', 3' and 4' lengths. Luminaire can be ordered with lamps, consult factory.

**Mounting:** Surface, individually or continuous rows.

**Labels:** UL / cUL listed. Damp location is optional.

**Ordering Information**

Sample: 17N-154T5HO-277-PSN-EM

Series	Lamp	Wattage	Voltage	Ballast		Options
17N	1 2	14T5	UNV 120 277 347 <sup>2</sup>	T5/T5HO	Ballast Factor	EM <sup>3</sup> Emergency Battery Pack DL Damp Location AL Aluminum Housing SS Stainless Steel Housing (Unfinished) QW Quick Through Wiring for Continuous Row Applications GLR Fusing
		24T5HO <sup>1</sup>		PS (Standard) Program Start	N Normal	
		21T5		HEPS <sup>2</sup> High Efficiency Program Start		
		39T5HO <sup>1</sup>		All Lamp Dimming Options		
		28T5		DIM <sup>2</sup> Dimming		
54T5HO <sup>1</sup>	SD <sup>2</sup> Step Dimming					

**Notes:**

- 1-lamp cross-section only.
- Consult factory.
- Specific voltage must be ordered for this option. Consult factory for nominal 2' and 3' units.

Typical plan view of 7/8" KOs on back of housing

3-3/4" Typ.

