

Length	Wattage
24"	14T5, 24T5HO, 17T8
36"	21T5, 39T5HO, 25T8
48"	28T5, 54T5HO, 32T8
72"	21T5-6, 39T5HO-6, 25T8-6
96"	28T5-8, 54T5HO-8, 32T8-8

Project Name:	
Type:	Date:
Catalog #:	

**Description:**

The Nulite S66 series is a surface mounted luminaire designed for many diffuser options. This series can be mounted individually or continuously, and is ideal for lobbies, corridors or office areas. Standard shielding is a prismatic lens.

**Specifications:**

**Construction:** Housing is die formed and welded of 20 gauge cold rolled steel and finished with white powder coat paint. Standard prismatic acrylic lens.

**Reflector / Ballast:** Ballast cover/reflector is finished with high reflectance white powder coat paint. Standard electronic, Class P, ballast. Universal (UNV) voltage ballast is from 120 to 277V.

**Lamping:** 1 or 2 lamp cross-section in nominal 2', 3', 4', 6' or 8' lengths. Luminaire can be ordered with lamp, consult factory.

**Mounting:** Ceiling, individually or continuous rows.

**Labels:** UL / cUL listed. Damp location is optional.

**Ordering Information**

Sample: S66-232T8-UNV-HEISL-WH-ASTN


Series	Lamp	Wattage	Voltage	Ballast	Color	Options
S66	1	14T5	UNV	T8 Options	WH White (Standard)  Consult factory for custom color.	EM <sup>2</sup> Emergency Battery Pack
		24T5HO	120	IS (Standard) Instant Start		N Normal (Standard)
	17T8	277	PS Program Start	L Low		ASTN Acrylic Satin Lens
	39T5HO	347 <sup>1</sup>	HEIS High Efficiency Instant Start	H High		AMLPA Acrylic MicroLinear Prismatic Lens
	25T8		HEPS High Efficiency Program Start			SPC1 Square Silver Parabolic (1/2")
	28T5					SPC2 Square Silver Parabolic (1-1/2")
	54T5HO		T5/T5HO	Ballast Factor		EC White Cube Louver (1/2")
	32T8		PS (Standard) Program Start	N Normal		CBW 1"H x 1" o.c. White Cross Baffle
	21T5-6		HEPS <sup>1</sup> High Efficiency Program Start			PBS 1-3/8"H x 2" o.c. Semi-specular Aluminum Parabolic Cross Baffle
	39T5HO-6			All Lamp Dimming Options		DL Damp Location
25T8-6		DIM <sup>1</sup> Dimming		QW Quick Through Wiring for Continuous Row Applications		
28T5-8		SD <sup>1</sup> Step Dimming		GLR Fusing		
54T5HO-8						
32T8-8						

Notes:

1. Consult factory.
2. Specific voltage must be ordered for this option. Consult factory for nominal 2' and 3' units.

**Photometric Curve**

Cat.# S66-132T8...  
 Initial lamp lumens - 2900  
 Prismatic lens and white reflector



*Specifications and dimensions are subject to change without notification.*