



Project Name:	
Type:	Date:
Catalog #:	

Description:

The Nulite 11G series is a commercial grade recessed grid mounted nominal 1'x1' luminaire with optional flange housing. Unit has a concealed latch hinge door with standard A12 prismatic lens.

Specifications:

Construction: Die formed housing of cold rolled steel. Housing is finished after fabrication with white polyester powder coat paint.

Reflector / Ballast: Ballast cover/pan is finished with high reflectance white powder coat paint. Standard electronic, Class P, ballast. Universal (UNV) voltage is from 120 to 277V.

Shielding: A12 prismatic lens standard. Optional - 4 cell parabolic louver.

Lamping: 1 or 2 lamp compact fluorescent. Luminaire can be ordered with lamps, consult factory.

Mounting: Grid ceiling, lay-in mounting. Optional flange for plaster-type ceiling with leveling lugs. Non-IC rated.

Labels: UL / cUL listed. Non-IC rated. Damp location is optional.

Ordering Information

Sample: 11G-226CFTR-277

Series	Lamp	Wattage	Voltage	Options
Grid 11G	1	18CFTR 18W/GX24q-2	UNV	EM ¹ Emergency Battery Pack
	2	26CFTR 26W/GX24q-3	120	BR Black Reveal
Flange 11F		32CFTR 32W/GX24q-3	277	PBS 4 Cell Parabolic Louver
		42CFTR 42W/GX24q-4		DL Damp Location
				GLR Fusing
				FLEX3 6' of Flex, 3-wire

Notes:

1. Specific voltage must be ordered for this option.