



Open with Clear Ribbed Lens

Project Name:	
Type:	Date:
Catalog #:	

Description:

The Nulite RAZ-O series is a rugged design, decorative, nominal 13" x 9" oval wall pack offered in 4 styles for compact fluorescent or HID sources which is ideal for commercial projects where aesthetics are important.

Specifications:

Construction: Die cast, marine grade aluminum housing with 3 depths depending on lamp wattage, threaded KO's on sides of deep housing and standard finish is bronze. Lens is injection molded UV stabilized translucent white polycarbonate with radial prisms. Lens and housing are gasketed with EPDM ribbed rubber to seal out moisture. Optional Lenses - Clear Ribbed or Frosted Ribbed. Optional injection molded guard - Cross or Eyelid.

Reflector / Ballast: Reflector/pan is formed and finished with high reflectance baked white enamel paint. Ballast is electronic for CFL and open core & coil for HID.

Lamping: 1 lamp compact fluorescent or pulse start metal halide. Luminaire can be ordered with lamp, consult factory.

Mounting: Surface. 1/2" conduit entry in back; 7-7/8" deep housing has threaded side entries.

Labels: UL / cUL listed, suitable for Wet Locations.


Guard Options:



Cross




Horizontal Eyelid



Vertical Eyelid



4" ⁽¹⁾



7-7/8" ⁽²⁾



Ordering Information

Sample: RAZO-132-277-BZ-HE-CLR-TP

Series	Wattage	Voltage	Color	Guard	Lens	Options
RAZO						
	Compact Fluorescent	UNV ³	BZ Bronze (Standard)	O Open (Standard)	WH White (Standard)	EM ⁴ Emergency Battery
	118CFQ ¹ (1) 18W/G24q-2	120				
	126CFQ ¹ (1) 26W/G24q-3		BK Black	C Cross	CLR Clear Ribbed	GLR Fusing
	132CFTR ¹ (1) 32W/GX24q-3	277				
	142CFTR ² (1) 42W/GX24q-4		WT White	HE Horizontal Eyelid	FR Frosted Ribbed	TP Tamper Resistant Hardware (Spanner head screws)
	Pulse Start Metal Halide		Consult factory for custom colors.	VE Vertical Eyelid		DEP 7-7/8" Deep Housing for CFL 1-light
	35MH ² 35W MH/MED					
	50MH ² 50W MH/MED					

Notes:

1. Luminaire depth is 3-3/4" without guard, 4" with guard.
2. Luminaire depth is 7-5/8" without guard, 7-7/8" with guard.
3. Universal voltage from 120 to 277V for compact fluorescent only.
4. Only available for compact fluorescent and nominal 7" deep housing.