


ARS Top View (Solid Cutoff)



CSV Top View (Sawtooth Cutoff)



Length	Lamping
22-1/2"	14T5, 24T5HO
34-3/8"	21T5, 39T5HO
46-1/8"	28T5, 54T5HO
92-1/4"	28T5-8, 54T5HO-8

**Ordering Information**

Sample: CSV-154T5HO-UNV-DL

Series	Lamp	Wattage	Voltage	Ballast	Options
ARS (Solid)	1	14T5 24T5HO	UNV 120	Blank = Program S. DIM <sup>1</sup> = Dimming	EM <sup>2</sup> Emergency Battery Pack DL Damp Location
CSV (Sawtooth)		21T5 39T5HO 28T5 54T5HO 28T5-8 54T5HO-8	277 347 <sup>1</sup>		

**Notes:**

1. Consult factory.
2. Emergency battery pack is not available for nominal 2' unit; consult factory for 3' unit. Emergency battery pack is not available for UNV voltage code. Specific voltage must be ordered for this option.

Project Name:	
Type:	Date:
Catalog #:	

**Description:**

The Nulite high performance cove luminaires are specification grade products. The ARS luminaire features a solid cutoff to reduce back-splash; the CSV luminaire features a "sawtooth" cutoff to soften the back-splash.

**Specifications:**

**Construction:** Die formed 20 gauge cold rolled steel with 7/8" end KO's. The housing is finished in high reflectance white baked polyester powder coat paint after fabrication.

**Reflector / Ballast:** Reflector is highly specular anodized aluminum. Standard electronic, class P, ballast. Universal (UNV) voltage ballast is from 120 to 277V.

**Lamping:** 1 lamp cross section T5 or T5HO. Luminaire can be ordered with lamps, consult factory.

**Mounting:** Surface mounting in architectural detail by others.

**Labels:** UL / cUL listed. Suitable for Damp Location optional.